

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	192.168.3.100	217.0.23.101	SIP	614	Request: REGISTER sip:tel.t-online.de (1 binding)
2	0.226706	217.0.23.101	192.168.3.100	SIP	529	Status: 401 Unauthorized 01033033C
3	0.306168	192.168.3.100	217.0.23.101	SIP	873	Request: REGISTER sip:tel.t-online.de (1 binding)
4	0.491742	217.0.23.101	192.168.3.100	SIP	733	Status: 200 OK (1 binding)



▶ Frame 4: 733 bytes on wire (5864 bits), 733 bytes captured (5864 bits) on interface 0

▶ Ethernet II, Src: [REDACTED]

▶ Internet Protocol Version 4, Src: 217.0.23.101, Dst: 192.168.3.100

▶ User Datagram Protocol, Src Port: 5060, Dst Port: 5060

▼ Session Initiation Protocol (200)

▶ Status-Line: SIP/2.0 200 OK

▼ Message Header

▶ Via: SIP/2.0/UDP 192.168.3.100:5060;branch=z9hG4bK.E7ZLNLFo-;rport

▼ From: <sip:+4951189711851@tel.t-online.de>;tag=VF5IDDev

▶ SIP from address: sip:[REDACTED]@tel.t-online.de

SIP from tag: VF5IDDev

▼ To: <sip:[REDACTED]@tel.t-online.de>;tag=h7g4EsbG_f785dcfc05ea5b6c10cde733c5bf8c3b

▶ SIP to address: sip:[REDACTED]@tel.t-online.de

SIP to tag: h7g4EsbG_f785dcfc05ea5b6c10cde733c5bf8c3b

Call-ID: FW78VGQZvN

▶ CSeq: 21 REGISTER

▼ Contact: <sip:[REDACTED];transport=udp>;expires=660;+sip.instance="<urn:uuid:bf7fe127-2be9-4e4f-acef-3093c3234073>"

▶ Contact URI: sip:+4951189711851@192.168.3.100;transport=udp

Contact parameter: expires=660

Contact parameter: +sip.instance="<urn:uuid:bf7fe127-2be9-4e4f-acef-3093c3234073>"\r\n

p-associated-uri: <sip:[REDACTED]@tel.t-online.de>

p-associated-uri: <tel:[REDACTED]>

▶ service-route: <sip:217.0.23.101:5060;transport=udp;lr>

▼ authentication-info: qop=auth, rspauth="46ec7dfe7216f02ff4a646b5397e0806", cnonce="0Hn50dh-fQdu6tqJ", nc=00000001

QOP: auth, rspauth="46ec7dfe7216f02ff4a646b5397e0806"

CNonce Value: "0Hn50dh-fQdu6tqJ"

Nonce Count: 00000001

Content-Length: 0